🔀 КУОСЕRа

Secure, sustainable affordable colour

Enjoy low running costs and high-quality prints with the ECOSYS PA2600cx/ECOSYS PA2600cwx. This is the ideal desktop printer for small companies and home workers. It has an intuitive touch screen and cutting-edge security features to optimise workflows.

								-				Job Box USB Dr			
			+				- 11					((+	
			+			<u>,</u>	!			L				+	
					KAC	ICERA					ECOSY	5 PA2600cwx			
											ľm cark neu		et a		
+											& K40CEI	Ra	E		
ECOSYS PA2600cx/ PA2600cwx															
Print speeds up to 26 ppm															
AirPrint, Mopria and Kyocera Mobile Print capabilities															
	Direct printing from USB flash memory devices														
		I													

GENERAL

KYOCERA ECOSYS Laser Colour Printer Operation panel: Color 2.7inch TFT Type: Desktop Engine speed: Up to 26 A4 pages per minute simplex (single-sided), Up to 13 A4 pages per minute duplex (both sides) Resolution: 1200 x 1200 dpi Recommended Print Volume¹ Average 900 images per month Maximum Print Volume¹: 65,000 pages per month Maximum Life¹: 100,000 pages or 5 years Warm-up time: Approx. 29 seconds or less (after switching on) Time to first print: Approx. 9.5/10.5 seconds or less b/w/colour CPU: ARM Cortex-A53 single core 1.0GHz Memory: Standard 1 GB Standard interfaces: USB 2.0 (Hi-Speed), Network (10BASE-T/100BASE-TX/1000BASE-T), WLAN (802.11a/b/g/n/ac, Wi-Fi Direct, 2.4/5 GHz)², USB host for USB flash memory, slot for optional SD/SDHC card Integrated accounting: 20 department codes Dimensions (W x D x H): Without packaging: 410 x 410 x 329 mm, With packaging: 596 × 571 × 459mm Weight: Without packaging: Approx. 25 kg (with bundled toner) Approx. 26 kg (without bundled toner) With packaging: 28 kg Power source: AC 220 ~ 240 V, 50/60 Hz Power consumption: Printing: 375 W Ready mode: 33 W Sleep-mode: 0.4 W Noise (sound pressure level: ISO 7779/ISO 9296): Printing: 63.1 dB(A) Quite mode: 48 dB (A) Stand-by: 29 dB(A) Safety standards: TÜV/GS, CE This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions. **Input capacity:** Multi-purpose tray: 50 sheets, 60–220 g/m², A6, A5, A4, custom (70 × 148 – 216 × 356 mm), Standard universal paper cassette: 250 sheets, 60–163 g/m², A6, A5, A4, custom (100 × 148 – 216 × 356 mm), Max. input capacity with options: 550 sheets. **Duplex:** Standard duplex unit, two-sided printing, 60–163 g/m², A5, A4, custom (140 × 210 – 216 × 356 mm). **Output capacity:** Max. 150 sheets (face-down) with paper full detection

PRINT FUNCTIONS

Controller language: PRESCRIBE Emulations: PCL 6 (5e, XL), KPDL3 (PostScript 3 compatible), PDF Direct Print 1.7, 2.0, XPS/Open XPS Direct Print, TIFF Direct Print

Operating systems: All current Windows operating systems, MAC OS X Version 10.9 or higher, Chrome OS, as well as other operating systems on request Fonts/barcodes: 93 outline fonts (PCL6, KPDL3), 4 fonts (Calibri), 4 fonts (Cambria), 1 Bitmap font, 45 onedimensional barcodes (e.g. EAN-8, EAN-13, EAN-128), as well as support for two-dimensional barcodes PDF417 under PRESCRIBE (PCL and other barcodes available an option) **Print features:** "Proof and hold"³, Job storage³, Quick copy³, Private print³, Data storage method with PIN code or password³, Internet printing IPP 1.0, E-mail printing, WSD Print, EcoPrint - toner save mode, AirPrint, Mopria, Microsoft Universal Print, Job batch output, Kyocera Cloud Access, optional Kyocera Cloud Print and Scan, Secure Boot, Run-time Integrity Check, Allowlisting, TL5 1.3, IPSec, HTTPS, SNMPV3, S/MIME, "Confidential printing" wSD plocal and network authentication, Windows authentication (NTLM v2, Kerberos), Restriction of the user group through user login administration, IP filtering, port number restriction, blocking of interfaces, Security Quick Setup, Administrator Authentication on Firmware Update, SIEM Support (SysLog), SCEP, OCSP/CRL, optional TPM (Trusted Platform Module) **Mobile printing support:** KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, Microsoft Universal Print, Wi-Fi Direct²

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752 **TK-5450K Toner Kit:** Microfine toner black for 4,100 pages A4. Capacity of starter toner is 1,500 pages A4. **TK-5450C, TK-5450M, TK-5450Y Toner Kit:** Microfine toner cyan, magenta, yellow for 3,200 pages A4 Starter toner cyan, magenta, yellow toner yield 1,500 pages A4

OPTIONS

PF-1100 Paper feeder (max. 1 units): Max. 250 sheets, 60 - 163 g/m²; A6, A5, A4, custom (105 mm × 148 mm - 216mm × 356mm)

ECURITY

UG-33: ThinPrint support IG-51: TPM (Trusted Platform Module), additional protection of confidential data USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available

WARRANTY

2-year warranty as standard³.3-year warranty on drum and developer.

KYOCERA LIFE

Up to 3-year on-site warranty extensions available for product and options.

WHAT'S IN THE BOX

Main unit, starter toner for 1,500 pages Black, Cyan, Magenta, Yellow, Quick Guide, safety instructions, power supply cord, power supply cord.

DVD with drivers, software and user manual not contain. Computer with internet connection for download the drivers and software required.

¹The device is not designed to achieve the specified volumes in continuous operation. ²Only ECOSYS PA2600cwx ³Optional SD/SDHC memory card is required

ECOSYS stands for ECOlogy, ECOnomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.





KYOCERA Document Solutions (UK) Ltd, Eldon Court, 75-77 London Road, Reading RG1 5BS T: 0333 015 1855, F: 0118 931 1108 E: info@duk.kyocera.com



* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

KYOCERA Document Solutions Partner



kyoceradocumentsolutions.co.uk