A2000 NVMe PCIe SSD

kingston.com/flashguide

Uncompromising performance, amazing value

Kingston's A2000 NVMe PCle SSD is an affordable storage solution with impressive performance. Boasting read/write speeds of up to 2,200/2,000MB/s¹, A2000 delivers 3x the performance of a SATA SSD with quicker loading times, less power consumption and lower heat. A2000 SSD is designed for the entry-level user, purpose-built system manufacturer, DIY system builder and those seeking to upgrade their PC. With a single-sided slim M.2 design, A2000 works to its full potential when installed in an Ultrabook or a small-form-factor PC (SFF PC) system.

Available in capacities from 250GB–1TB² to meet your system's needs. A2000 is a self-encrypting drive that supports end-to-end data protection using 256-bit XTS-AES hardware-based encryption, and allows the use of independent software vendors with TCG Opal 2.0 security management solutions such as Symantec™, McAfee™, WinMagic® and others. A2000 also has built-in eDrive support, a security storage specification for use with BitLocker.

- NVMe PCIe performance at a fraction of the cost
- > Supports a full-security suite (TCG Opal, XTS-AES 256-bit, eDrive)
- > Ideal for Ultrabooks and small-formfactor PC (SFF PC) systems
- > Upgrade your PC with up to 1TB²



Features/specs on reverse >>



A2000 NVMe PCIe SSD

FEATURES/ BENEFITS

- > NVMe PCIe performance at a fraction of the cost A2000 is an affordable solution with impressive read/write speeds of up to 2,200/2,000MB/s¹.
- > Full-security suite Protect and secure your data with Kingston's self-encrypting drive.
- > **Optimal systems** Ideal for Ultrabooks and small-form-factor PC (SFF PC) systems.
- > Multiple capacities Upgrade your PC with up to 1TB².

SPECIFICATIONS

- > Form factor M.2 2280
- > Interface NVMe™ PCle Gen 3.0 x 4 lanes
- > Capacities² 250GB, 500GB, 1TB
- >**NAND** 3D
- > **Encrypted** XTS-AES 256-bit encryption
- > Sequential read/write1

250GB – up to 2,000/1,100MB/s 500GB – up to 2,200/2,000MB/s

1TB - up to 2,200/2,000MB/s

> Random 4K read/write¹

250GB – up to 150,000/180,000 IOPS 500GB – up to 180,000/200,000 IOPS 1TB – up to 250,000/220,000 IOPS

> Total Bytes Written (TBW)3

250GB – 150TBW 500GB – 350TBW 1TB – 600TBW

> Power consumption

.0032W idle / .08W avg / 1.7W (MAX) read / 4.5W (MAX) write

- > Storage temperature -40°C~85°C
- > Operating temperature 0° C \sim 70 $^{\circ}$ C
- > **Dimensions** 80mm x 22mm x 3.5mm
- > Weight

250GB - 6.6g

500GB - 6.8q

1TB - 6.6g

- > Vibration operating 2.17G peak (7-800Hz)
- > Vibration non-operating 20G peak (20-1000Hz)
- > MTBF 2,000,000
- > Warranty/Support⁴

limited 5-year warranty with free technical support



PART NUMBERS

SA2000M8/250G SA2000M8/500G SA2000M8/1000G

The cryptographic functions mentioned in the present section are implemented in the firmware of the product. The cryptographic functions of the firmware can be changed only during the manufacturing process and cannot be changed by a standard user. The product is designed for installation by the user in accordance with the step-by-step instructions in the installation user guide supplied with the product. It can therefore be used without further substantial support from the supplier.

The SSD is designed for use in desktop and notebook computer workloads, and is not intended for server environments.

- Based on "out-of-box performance" using a PCIe 3.0 motherboard. Speed may vary due to host hardware, software and usage. IOMETER random 4K read/write is based on an 8GB partition.
- Some of the listed capacity on a Flash storage device is used for formatting and other functions and is
 thus not available for data storage. As such, the actual available capacity for data storage is less than
 what is listed on the products. For more information, go to Kingston's Flash memory guide at
 kingston.com/flashguide.
- 3. Total Bytes Written (TBW) is derived from the JEDEC Client Workload (JESD219A).
- 4. Limited warranty based on 5 years or "Percentage Used", which can be found using the Kingston SSD Manager (Kingston.com/SSDManager). For NVMe SSDs, a new unused product will show a Percentage Used value of 0, whereas a product that reaches its warranty limit will show a Percentage Used value of greater than or equal to one hundred (100). See Kingston.com/wa for details.



