

High Speed Mini-HDMI Cable (M/M), 6 ft.

MODEL NUMBER: P572-006



Highlights

- Supports HD video resolutions up to 1080p
- Premium foil and braid shielding protects against EMI/RFI noise
- 24K gold-plated connectors for maximum conductivity

Package Includes

Mini-HDMI to Mini-HDMI Cable - M/M, 6 ft.

Description

Tripp Lite's six-foot Mini-HDMI to Mini-HDMI cable allows you to connect digital cameras, camcorders and other digital devices with the Mini-HDMI connector directly to your standard Mini-HDMI-enabled TV. Cable increases bandwidth to 340 MHz or about 10.2 Gbps. This means you get a more consistent, clean audio and video signal from point A to point B. 24K gold-plated connectors ensure the ultimate in error free signal transfer. RoHS compliant.

Features

Connects Mini-HDMI Devices

- Recommended for mobile users who want a cable that can easily pack away in a backpack, laptop bag
 or camera bag
- Ideal for connecting a mini-HDMI camcorder, digital camera or tablet to an mini HDMI display

High Performance and Wide Compatibility

- Supports HD video resolutions up to 1080p
- Superior Quality Ensures a Flawless Signal
- 24K gold-plated connectors and contacts for maximum conductivity and minimum data loss
- Integral strain relief protects cable and connectors from stress and cracking
- Foil and braid shielding protects against EMI/RFI line noise that can distort or destroy data
- Flexible PVC jacket easy to install in tight spaces

Specifications

OVERVIEW		
UPC Code	037332137920	
Product Type	Passive	
Technology	HDMI	
VIDEO		





Max Supported Video Resolution	1920 x 1080 @ 60Hz	
Max Supported Color Depth	48-bit Deep Color	
HDR Support	No	
3D Video Supported	No	
Chroma Sub Sampling	4:4:4	
EDID Support	Yes	
Signal Transmission	Bidirectional	
AUDIO		
Audio Specification	DTS-HD	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	0	
PHYSICAL		
Material of Construction	PVC	
Color	Black	
Cable Jacket Color	Black	
Connector Color	Black	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	5.5mm	
Wire Gauge (AWG)	30	
Cable Length (ft.)	6	
Cable Length (m)	1.83	
Ferrite Core	No	
Minimum Bend Radius	27.5mm	
Shipping Dimensions (hwd / cm)	0.64 x 17.78 x 22.86	
Shipping Dimensions (hwd / in.)	0.25 x 7.00 x 9.00	
Shipping Weight (kg)	0.05	
Shipping Weight (lbs.)	0.10	
ENVIRONMENTAL		
Operating Temperature Range	14 to 122 F (-10 to 50 C)	
Storage Temperature Range	5 to 140 F (-15 to 60 C)	
Operating Humidity Range	0% to 90% RH, Non-Condensing	
Storage Humidity Range	0% to 90% RH, Non-Condensing	





COMMUNICATIONS		
EDID Compatible	Yes	
Consumer Electronics Control (CEC) Supported	Yes	
CONNECTIONS		
Side A - Connector 1	MINI HDMI (MALE)	
Side B - Connector 1	MINI HDMI (MALE)	
Connector Plating	Gold	
Contact Plating	Gold	
Connector Style	Straight	
Gripping Connector	No	
FEATURES & SPECIFICATIONS		
HDCP Specification	1.4; 2.2	
EMI/RFI Line Noise Protection	No	
MST Support	No	
IP68 Rated	No	
Antibacterial	No	
Armored Cable	No	
Ethernet Support	No	
STANDARDS & COMPLIANCE		
Certifications	RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies