

USB-C to VGA and HDMI Adapter - 2-in-1 - 4K 30Hz - Space Grey

Product ID: CDP2HDVGA



This USB-C to VGA and HDMI adapter offers a portable solution for connecting your USB Type-C laptop to a VGA or HDMI display. The multiport video adapter also works as a splitter, enabling you to simultaneously output an identical video signal to two separate monitors (1 x HDMI and 1 x VGA).

Two-in-One Video Connectivity with Travel in Mind

Avoid the hassle of carrying different adapters, with a 2-in-1 USB-C monitor adapter. With VGA, and HDMI outputs, you can conveniently connect your laptop to any HDMI or VGA-equipped display, using this multiport adapter.

The adapter features a durable aluminum enclosure and can withstand being carried in your travel bag.

Ultra HD 4K 30Hz Resolution

The HDMI output on this USB-C video adapter supports UHD resolutions up to 4K 30Hz, while the VGA output supports HD resolutions up to 1920 x 1200.

Stylish Connectivity for Your MacBook, MacBook Pro, or Any Laptop

The USB-C video adapter has a Space Gray housing and built-in USB-C cable designed to match your Space Gray MacBook or MacBook Pro. The adapter is compatible with USB-C DP Alt Mode devices.

CDP2HDVGA is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Connect to virtually any VGA or HDMI display while traveling
- Use as a video splitter to output an identical image to a VGA and HDMI monitor simultaneously splitting the image
- Output video to a secondary VGA, or HDMI monitor

Features

- Maximize your laptop's video compatibility with a 2-in-1 adapter: USB-C to HDMI® and VGA
- Support resource-demanding applications with UHD resolutions up to 4K 30Hz
- Space Gray adapter matches your Space Gray MacBook or MacBook Pro

| | | |
|---------------------------------|-------------------------------------|---|
| Hardware | Warranty | 3 Years |
| | Active or Passive Adapter | Active |
| | Adapter Style | Adapters |
| | AV Input | USB Type-C |
| | AV Output | HDMI VGA |
| | Chipset ID | ITE - IT6222 |
| Performance | Audio Specifications | HDMI output: 5.1 surround sound |
| | Maximum Analog Resolutions | 1920 x 1200 @ 60Hz (VGA) |
| | Maximum Digital Resolutions | 3840 x 2160 @ 30Hz (HDMI) |
| | Supported Resolutions | Maximum HDMI output: 3840 x 2160 @ 30Hz Maximum VGA output: 1920 x 1200 @ 60Hz <i>Lower resolutions and refresh rates may also be supported</i> |
| | Video Revision | HDMI 2.0 |
| Connector(s) | Connector A | 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input |
| | Connector B | 1 - VGA (15 pin, High Density D-Sub) Female Output 1 - HDMI (19 pin) Female Output |
| | Special Notes / Requirements | Note HDMI and VGA can output video at the same time. If both video outputs are connected, they'll display the same image at a maximum resolution of 1920x1200 @ 60Hz The HDMI port is a passive port. The VGA port is an active port. |
| Environmental | Humidity | 5~90% RH |
| | Operating Temperature | 0°C to 45°C (32°F to 113°F) |
| | Storage Temperature | -10°C to 70°C (14°F to 158°F) |
| Physical Characteristics | Accent Color | Black |
| | Cable Length | 6 in [152.4 mm] |
| | Color | Space Gray |
| | Enclosure Type | Aluminum and Plastic |
| | Product Height | 0.6 in [16 mm] |
| | Product Length | 2.4 in [62 mm] |
| | Product Weight | 3.2 oz [90 g] |

| | | |
|------------------------------|---------------------------|------------------------|
| | Product Width | 1.4 in [36 mm] |
| Packaging Information | Shipping (Package) Weight | 0.2 lb [0.1 kg] |
| What's in the Box | Included in Package | 1 - Travel A/V Adapter |

Product appearance and specifications are subject to change without notice.