Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Wiz

Supplier's address: WiZ, WiZ I.B.R.S. / C.C.R.I. Number 10461, 5600VB Eindhoven, NL

Model identifier: 9290023838AW

Type of light source:

	1		
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	B22		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Devenator		Value	Devenueter	Mahua		
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/100 up to the nearest	0 h), rounded	8	Energy efficiency class	F		
Useful luminous indicating if it ref in a sphere (360 cone (120 ^o) or in (90 ^o)	fers to the flux Dº), in a wide	806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	22006500		
On-mode po expressed in W	ower (P _{on}),	8,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,50		
Networked stand for CLS, express rounded to the se	ed in W and	0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	90		
Outer	Height	120	Spectral power	See image		
dimensions	Width	60	distribution in the	in last page		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	60	range 250 nm to 800 nm, at full-load			
Claim of equival	lent power ^(a)	Yes	If yes, equivalent power (W)	60		
			Chromaticity coordinates (x and y)	0,458 0,410		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	0	Survival factor	0,90		
the lumen main	tenance factor	0,96				
Parameters for	LED and OLED ma	ains light sources:				
displacement fa	ctor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6		
source replaces	an LED light s a fluorescent hout integrated icular wattage.	_(b)	If yes then replacement claim (W)	-		
Flicker metric (P	Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)'-' : not applicable;

(b)'-' : not applicable;

