

MSA Uncoded SFP Transceiver Module - 100BASE-BX - 100 MbE Gigabit Ethernet BiDi Fiber (SMF)

Product ID: SFP100BBXDST



• Wavelength: 1550nmTx/1310nmRx

• Maximum Data Transfer Rate: 155 Mbps

• Type: Single Mode Fiber

• Connection Type: LC Connector

• Maximum Transfer Distance: 10 km (6.2 mi)

• Power Consumption: Less than 1 Watt

• DDM: Yes

This SFP fiber module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP Cables, providing the convenience and reliability you need to ensure dependable network performance.

## **Certifications, Reports and Compatibility**















## **Applications**

- Replace defective or damaged SFP modules
- Expand your network to remote segments

## **Features**

- MSA UNCODED SFP TRANSCEIVER: 100Mb Ethernet BiDi Fiber Single Strand SFP designed, programmed and tested to work with compatible MSA Compliant switches and routers to deliver reliable 100MbE connectivity
- INCREASE BANDWIDTH ON EXISTING INFRASTRUCTURE: This 1 Gigabit Ethernet bi-directional WDM SFP+ transceiver module sends and receives over a single strand of fiber optic cable instead of two.
- TECHNICAL SPECS: 100BASE-BX 100Mbps 100Mb Bi-Directional Downstream Single Mode (SMF) LC Connector 1550nmTx/1310nmRx Digital Diagnostic Monitoring (DDM) Distances up to 10km (6.2mi).
- WORKS WITH MSA COMPLIANT SWITCHES: Works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncoded modules
- THE IT PRO'S CHOICE: Designed and built for IT Professionals, this SFP module is backed for life (lifetime of module, not network switch), including free lifetime 24/5 multi-lingual technical assistance

Hardware

Lifetime Warranty

Compatible Brand MSA Compliant

**WDM** Yes

**Industry Standards** IEEE 802.3u 100BASE-BX

**Performance** 

Maximum Data Transfer

Rate

155 Mbps

Max Transfer Distance 10 km (6.2 mi)

Type Single Mode

1550nmTx/1310nmRx Wavelength

Fiber Operating Mode Half/Full-Duplex



DDM Yes

Compatible Networks 100 Mbps

Power Consumption (In

Watts)

< 1 W

Connector(s)

Local Unit Connectors 1 - Fiber Optic LC Duplex

Special Notes / Requirements

Note For use in 100 Mbps fiber networking equipment and media

converters

**Environmental** 

Operating Temperature 0C to 70C (32F to 158F)

Storage Temperature -40C to 85C (-40F to 185F)

Humidity 5~95% RH

Physical Characteristics

Product Length 2.4 in [60.0 mm]

Product Width 0.6 in [16.0 mm]

Product Height 0.4 in [1.1 cm]

Weight of Product 0.6 oz [18.0 g]

Packaging Information

Package Length 4.6 in [11.7 cm]

Package Width 3.6 in [92.0 mm]

Package Height 1.2 in [30.0 mm]

Shipping (Package)

Weight

1.7 oz [47.0 g]

What's in the Box

Included in Package 1 - SFP transceiver



\*Product appearance and specifications are subject to change without notice.