SMART.

Specifications SMART Board[®] MX055-V2 interactive display with iQ Model SBID-MX255-V2

Overview


The SMART Board® MX055-V2 interactive display with iQ has all the essentials educators need for bringing the devices students love into any learning environment. This display is a great value for schools that need an interactive display on a budget. The 55" 4K Ultra HD resolution display includes a one-year subscription to SMART Learning Suite and a standard three-year warranty.



The iQ experience offers one-touch access to SMART Learning Suite applications, including SMART Notebook[®] lessons and activities. You can also access collaboration tools, including a digital whiteboard, a web browser, and wireless screen sharing.

Dimensions and weights¹

Dimensions



Weight

75 lb. 12 oz. (34.4 kg) Active touch area 49 3/16" × 28 3/8" (125 cm × 72 cm) Active image area 47 5/8" × 26 3/4" (121 cm × 68 cm) Shipping dimensions (including pallet)² 56" W × 35 5/8" H × 9 3/8" D (142.3 cm× 90.4 cm × 23.5 cm) Shipping weight (including pallet) 113 lb. (51.1 kg)



As an ENERGY STAR[®] certified signage display, the SMART Board MX055-V2 interactive display meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

 $^1\mbox{All}$ dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg). $^2\mbox{Product}$ ships upright.

Hardware

Interaction

Touch technology	HyPr Touch [™] with Advanced IR
Multitouch capabilities	Up to 20 simultaneous touch, writing, or erase points ^{3 4}
Object Awareness™	Behavior adjusts automatically to the tool or object you're using, whether it's a pen, finger or palm.
Positioning accuracy	<2 mm
Display	
Туре	LED backlit LCD (A grade)
Aspect ratio	16:9
Resolution	4K UHD (3840 × 2160)
Horizontal frequency	31 Hz–140 kHz
Vertical frequency	59 Hz–70 Hz
Brightness (maximum)	350 cd/m ²
Refresh frequency	60 Hz
Pixel clock (maximum)	590 MHz
Pixel dimensions	0.37 mm
Viewing angle	178°
Response time (typical)	≤8 ms
Ambient light sensor	Yes
Bluetooth®	Bluetooth 4.2 dual mode (backwards compatible with Bluetooth 2.1 + EDR)
Audio	15 W integrated speakers (×2)
Wireless	IEEE 802.11a/b/g/n/ac with 2×2 MIMO (both 2.4 and 5 GHz bands) supporting WEP, WPA, WPA2 PSK, and 802.1X EAP authentication protocols
Included cables and accessories	Country-specific power cable 16' 5" (5 m) USB cable Wall mount bracket kit Pen (×2) Antenna (×2) IR remote control (with two AAA batteries)
Mounting holes	For a standard VESA® 400 mm × 400 mm mounting plate with M8 screws
Mounting bracket depth	Minimum clearance depth of 11/4" (3 cm) for all components on the back of the interactive display for airflow

³Requires the latest version of SMART Product Drivers. Some applications might not support all touch points.

⁴Chrome OS is limited to 10 simultaneous touches. Pens and eraser are not supported.

iQ experience

iQ experience	iQ experience embedded in the display provides a separate appliance	better performance without the need to install
Included apps and features	Customizable Home screen Whiteboard SMART Notebook Player Browser Screen Share File and app libraries Writing and drawing over any input Freeze screen and screen shade Automatic software updates	
Supported languages	Chinese (simplified) Chinese (traditional) Czech Danish Dutch English Estonian Finnish French German Greek Hungarian Italian Japanese	Korean Latvian Lithuanian Norwegian Polish Portuguese Romanian Russian Slovak Slovenian Spanish Swedish Ukrainian Vietnamese Welsh
Software		
Included software	iQ Android-based embedded computing SMART Ink® and SMART Product Drivers	

SMART Notebook® basic version

Bonus one-year subscription to SMART Learning Suite (including SMART Notebook software) SMART Remote Management (subscription for length of included warranty) Connectors

Side connector panel	1	Accessory slot (for 60W OPS devices)
	1	HDMI [®] 2.0 out with HDCP 2.2 support ⁵
	1	USB 2.0 Type-A (for service use only)
	1	USB 3.0 Type-A (for currently selected input source)
	HD	DMI 1
	1	HDMI 2.0 in with HDCP 1.4 and HDCP 2.2 support
	1	USB 3.0 Type-B (for touch)
	HD	DMI 2
	1	HDMI 2.0 with HDCP 1.4 and HDCP 2.2 support
	1	USB 3.0 Type-B (for touch)
Front connector panel	1	USB 2.0 Type-A (for the display)
	1	USB 2.0 Type-A (for currently selected input source)
	HD	DMI 3
	1	HDMI 2.0 in with HDCP 1.4 and HDCP 2.2 support
	1	USB 2.0 Type-B (for touch)
Bottom connector	1	RS-232
panel	2	RJ45
	1	S/PDIF out (fixed)
		on bir out (inter)
	1	Stereo 3.5 mm out (variable)
	-	
	-	Stereo 3.5 mm out (variable)
	VG	Stereo 3.5 mm out (variable) GA 1

Installation requirements

Interactive display See the SMART Board MX (V2) and MX (V2) Pro series interactive displays installation and maintenance guide (smarttech.com/kb/171555)

IMPORTANT

The display needs an internet connection for downloading and installing important updates. Ask the network administrator to configure the network correctly for the iQ experience. For more information about network configuration, see Connecting a SMART display with the iQ experience to a network.

Room computers and guest laptops

General requirements	See SMART Notebook software release notes
4K UHD	Video card that can support 3840 × 2160 resolution at 60 Hz
	See Minimum requirements for Ultra High Definition or 4K on your interactive flat panel

⁵HDCP is always enabled. Content is shown in 480p resolution if the external display doesn't support HDCP.

Cable requirements

HDMI	Maximum length: 23' (7 m)
	NOTES
	 A certified Premium High Speed HDMI Cable is required for a display resolution of 3840 × 2160 at more than 30 Hz (such as 50 or 60 Hz).
	• The performance of cables longer than 23' (7 m) is highly dependent on the cable's quality.
USB 2.0	USB 2.0 certified Hi-Speed (480 Mbps) support Maximum length: 16' (5 m)
USB 3.0	USB 3.0 certified SuperSpeed (5 Gbps) support Maximum length: 9' (3 m)
	NOTES
	 SMART supports only installations that use directly connected video and USB cables, AC-powered extenders, or USB extenders purchased from SMART.
	• You might be able to use higher-grade cables that are longer than specified. If you have problems with such a cable or an extender of any type, test the connection with a shorter cable before contacting SMART Support.
Important	Using cables that exceed these maximum lengths can produce unexpected results, such as degraded picture quality or USB connectivity. Refer to <i>Installation best practices for SMART products</i> (smarttech.com/kb/171035) for comprehensive information about cables and extensions for SMART hardware products.

Storage and operating requirements

Power requirements	100V to 240V AC, 50 Hz to 60 Hz	
Standalone interactive display po	wer consumption at 77°F (25°C)	
Standby mode	<0.5 W	
Normal operating (out-of-box)	98 W	
Operating temperature	41–95°F (5–35°C)	
Storage temperature	-4–140°F (-20–60°C)	
Humidity	5–80% relative humidity, non-condensing	

Certification and compliance (partial)⁶

U.S. / Canada	UL, FCC, ISED, CONEG Packaging, Proposition 65
EU / EEA / EFTA / UK	CE, UKCA, LVD, CB, EMCD, RED, REACH, RoHS, Battery, WEEE, Packaging, POP, Ecodesign
Australia / New Zealand	RCM
Performance standards	ENERGY STAR®, HDMI, USB

Purchasing information

Order number

SBID-MX255-V2	SMART Board MX055-V2 interactive display with iQ and one-year subscription of SMART Learning Suite
Optional accessories	
Other	See smarttech.com/accessories

Warranty information

SMART Assure warranty Includes advanced hardware replacement and access to onsite support. Terms and conditions vary by region. Contact your local reseller or distributor for information and visit smarttech.com/warranty.

smarttech.com/support smarttech.com/contactsupport

© 2021 SMART Technologies ULC. All rights reserved. SMART Board, SMART Notebook, Pen ID, HyPr Touch, Object Awareness, Silktouch, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. The Bluetooth word mark is owned by the Bluetooth SIG, Inc. and any use of such marks by SMART Technologies ULC is under license. The Adopted Trademarks HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. February 17, 2021.

⁶Product availability may vary by region.