

42U Server Rack Cabinet - 36 in. Deep Enclosure

Product ID: RK4236BKB



This 42U server rack cabinet provides secure storage space for storing EIA-310 compliant 19" rack-mount devices such as Dell, HP and IBM servers, as well as telecommunication and A/V equipment. The server rack provides an economical yet robust solution, with a total load capacity of 907 kg (2000 lb.).

Hassle-free equipment installation

This network rack comes assembled, providing hassle-free deployment.

With adjustable mounting rails, you can easily change the rail depth from 6 to 36 in. (152.4 mm - 914.4 mm) to support full-depth equipment. The extra depth also supports additional cable and power management behind your equipment.

Both the top and bottom panels have removable cable-access covers which provide easy access for cable management. The rack also features a grounding wire, which can be used in the front or rear, enabling you to ground your equipment for added protection.

Keep your equipment secure, cool, and accessible



Data Sheet

To help keep your rack-mounted equipment secure, this rack features a reversible front door allowing for different rack configurations. The front and rear doors are both lockable, and the mesh design increases airflow to provide passive cooling.

The rack also has easily removable and lockable side panels, which allow for quick access to your equipment while still keeping it secure.

Maximum maneuverability, with casters included

The enclosure cabinet comes with both casters and leveling feet already installed, providing ease of mobility around your office, studio, or server room. Additionally, the width and height of the rack fit through standard doorways, providing the freedom to move your rack as needed.

The RK4236BKB is backed by a StarTech.com 5-year warranty and free lifetime technical support.



Data Sheet

Certifications, Reports and Compatibility



Applications

- Deploy in server rooms and data centers to maximize space and keep your equipment secure
- Install rack-mount servers, KVM switches, networking equipment and cabinet consoles
- House rack-mount audio/video equipment for broadcasting in your editing room or television studio

Features

- Easy equipment installation with adjustable mounting depth
- Keep equipment secure with locking front and back doors and side panels
- Preinstalled casters and levelling feet provide easy maneuverability
- Total load capacity of 907 kg (2000 lb.)
- Passive cooling mesh doors
- Hassle-free cable management



Hard-to-find made easy*

Data Sheet

	Warranty	5 Years
Usuduraus	-	
Hardware	Adjustable Mounting Rails	Yes
	Adjustable Size of Built-in Leveling Feet	100 mm [3.94 in]
	Back Door Construction	Steel Mesh
	Back Door Key Lock	Yes
	Back Door Reversible and/or Removable	Νο
	Cable Management	Yes Cable Access Covers
	Casters	Included
	Fan(s)	No
	Frame Type	Enclosed Cabinet
	Front Door Construction	Steel Mesh
	Front Door Key Lock	Yes
	Front Door Reversible and/or Removable	Reversible
		Removable
	Industry Standards	EIA-310-D
	Ladder Offset	0.4 in [10 mm]
	Ladder Type	G-Shape
	Mounting Holes	Square
	Number and Type of Included Cage Nuts	50 - M6
	Rack Type	4-Post
	Side Panel Construction	Solid Steel
	Side Panel(s) Key Lock	Yes
	Side Panels Reversible and/or Removable	Removable
	Style	Floor-Standing
	U Height	42U
	U Markings	Yes
	Wallmountable	No
Performance	Weight Capacity (Stationary)	2004.5 lb [907 kg]



Hard-to-find made easy*

	Data Sheet	
0.7 in [205.1 cm]		

Physical Characteristics	Height with Casters	80.7 in [205.1 cm]
	Maximum Mounting Depth	36.4 in [92.5 cm]
	Minimum Mounting Depth	5.9 in [15 cm]
	Product Height	75.7 in [192.2 cm]
	Product Length	39.4 in [100 cm]
	Product Width	23.6 in [60 cm]
Packaging Information	Flat Pack (Assembly Required)	No
	Shipping (Package) Weight	344.8 lb [156 kg]
What's in the Box	Included in Package	1 - enclosure cabinet
		50 - M6 screws
		50 - M6 cage nuts
		50 - washers
		1 - hex key
		2 - side-panel keys
		2 - door keys
		1 - instruction manual

Product appearance and specifications are subject to change without notice.