HANNspree

Experts in **Display**

HS 322 UPB (Model No. HSG1408)

80 cm / 31.5" Diagonal LED Backlight – Format 16:9

- 31.5" 16:9 LED Backlight Monitor
- 2560 x 1440 WQHD Resolution
- 178° / 178° Ultra-Wide Viewing Angle
- Digital Inputs: HDMI + DP
- Picture In Picture / Picture by Picture
- USB 3.0 HUB, 1 up 4 down
- Built-In Stereo Speakers
- Tilt and Wall-Mountable (VESA)
- Low Power Consumption
- Multi-Video Modes
- Low Blue Light Mode
- Flicker Free





80 cm / 31.5"

Part. No..: HS 322 UPB

SIZE, RESOLUTION

32.0"

32"

16:9 Aspect Ratio



WQHD 2560 x 1440

CONNECTIVITY



HDMI DP



Built-In Speakers

VIEWING ANGLE, VESA



178° Ultra-Wide Viewing Angle



VESA Wall-Mountable

OTHER FEATURES



USB 3.0 HUB







PBP

Display Solutions

Technical Specifications >>>

HANNspree

Experts in **Display**

Display Size	80cm / 31.5" Diagonal	
Panel Type	TFT – LED Backlight	
Aspect Ratio	16:9	
Resolution (H x V)	2560 x 1440 WQHD	
Brightness	350cd/m²	
Contrast (Typ.)	1.200:1 (Typical)	
Contrast (Active)	80.000.000:1 (Active)	
Viewing Angle L/R; U/D	178° H – 178° V (CR >10)	
Response Time	5 msec (with OD)	
Pixel Pitch	0,272 (H) x 0,272 (V) mm	
Panel Surface	Anti-Glare	
Display Colors	1.07B Colors	
Horizontal Frequency	30 ~ 138 kHz	
Vertical Frequency	48 ~ 75 Hz	
Max Display Frequency	2560 x 1440 @ 60Hz	
Input 1	HDMI 2.0	
Input 2	DP 1.2	
Audio I/O	Audio In (via HDMI/DP); Audio Out 3.5mm jack	
Buil-in Speakers	Yes, 2W x 2; Earphone Jack	
Power Consumption	On Mode: 30.91W; Sleep Mode: 0.30W; Off Mode: 0.24W (ETEC Total Energy Consumption. ENERGY STAR® Program Requirements for Displays Version 7.1)	
AC Power Range	AC 100 ~ 240 Volt; 50 ~ 65 Hz	
Product Dimensions	724,8 x 168,2 x 528,2 mm (W x D x H)	
Packing Dimensions	806 x 146 x 514 mm (W x D x H)	
Net / Gross Weight	6,6 Kg / 9,3 Kg (±0.3KG)	
Bezel & Color Plan	Black texture: front bezel, back cover, arm, base	

VESA Mounting	100 x 100 mm	
Monitor Stand	Fixed Stand	
Tilt / Kensington Lock	-5° ~ 15° / Yes	
Pivot / Swivel	-/-	
Controls	Menu, (-), (+), AUTO, Power	
Color	9300K, 6500K, 5500K, User Modes, Low Blue Light Mode	
Preset Mode	PC, Movie, Game, ECO Modes	
On Screen Display	11 OSD Languages	
Accessory	Power Cable (1,5m); HDMI Cable (1,5m); USB 3.0 Cable B-A (1m); Warranty Card; Quick Start Guide	
Other Features	USB 3.0 HUB (1 Upstream; 4 Downstream) Picture In Picture / Picture by Picture Low Blue Light Mode / Flicker Free	





Supplier's Name	HANNspree
Model Name	HS322UPB
Energy efficiency class for standard Dynamic Range (SDR)	G
Annual Energy Power Consumption (kWh/1000h)	38 kWh/1000h
On mode power demand for Standard Dynamic Range (SDR)	38 W
Off mode power demand (W)	0,2 W
Standby mode power demand (W)	0,3 W
Screen Diagonal (cm / inches)	80 cm / 31.5"
Resolution	2560 x 1440

PART. NO.: HS 322 UPB (Model No. HSG1408) 4 711404 023187 >

^{* &}quot;ADS" word mark / trademark and related patents on technologies belong to their respective owners.



^{**} USB 3.0: 1 upstream, 4 downstream, only one USB port for charging, Max 900mA